MINORE® -now supplied with natural refrigerant R290

Compact and economical



The MINORE® is a small circulatory cooler available in 300W, 350W and 500W versions. A cooling unit cools the circulating water and/or antifreeze mixture in a small container, from where it is supplied to the cooling unit by a circulation pump.

The container is easily accessible and can be filled from under the hinged cover on the top of the unit.

This type of unit is available in the same size of casing up to 600 W and 3.0 bars pump pressure and can be supplied as an air or water cooled version. Other temperature ranges are available.

Application examples

- Rotary evaporators
- Distillation devices
- Soxhlet extractions
- Water baths

Features and advantages

- 100% water savings in tap water
- No sewage costs for waste water
- Cooling water temperature, pressure and flow can be regulated
- Constant water quality, no limescale, no algae

- Minimum space requirement on every laboratory table
- Compact 5 litre tank
- Almost noiseless
- Temperature display in O-LED capacitive touch pad controller
- Lockable castors
- Acoustic and text description alarm Display
- Ambient temperature up to 32°C
- Available with higher pump pressure and many different options and accessories
- Power regulation by microprocessor controlled heating, this means high temperature stability of water pre-run temperature optional (0.1 K/°C)

Technical Data

MINORE® 0	MINORE® I	MINORE® II
16-22° C	16-22° C	16-22° C
300 watt	350 watt	500 watt
28 l/min.	28 l/min.	28 l/min.
0.4 bar	0.4 bar	0.4 bar
Quick lock with 9 mm	Quick lock with 9 mm	Quick lock with 9 mm
hose sleeves	hose sleeves	hose sleeves
360 x 470 x 590 mm	360 x 470 x 590 mm	360 x 470 x 590 mm
230 V/50 Hz/1 PH	230 V/50 Hz/1 PH	230 V/50 Hz/1 PH
220 Watt max.	270 Watt max.	340 Watt max.
31 kg	37 kg	38 kg
R290	R290	R290
MINORE® 0-A-RB400	MINORE® I-A-RB400	MINORE® II-A-RB400
MINORE® 0-W-RB400	MINORE® I-W-RB400	MINORE® II-W-RB400
	16-22° C 300 watt 28 l/min. 0.4 bar Quick lock with 9 mm hose sleeves 360 x 470 x 590 mm 230 V/50 Hz/1 PH 220 Watt max. 31 kg R290 MINORE® 0-A-RB400	16-22° C16-22° C300 watt350 watt28 l/min.28 l/min.0.4 bar0.4 barQuick lock with 9 mmQuick lock with 9 mmhose sleeveshose sleeves360 x 470 x 590 mm360 x 470 x 590 mm230 V/50 Hz/1 PH230 V/50 Hz/1 PH220 Watt max.270 Watt max.31 kg37 kgR290R290MINORE® 0-A-RB400MINORE® I-A-RB400